

Overview:

The **NETRO NN-EPON-8OLT** is self-developed Compact 1U EPON OLT equipment, meeting the requirements of IEEE802.3ah and meets the EPON OLT equipment requirements of YD/T 1945-2006 Technical requirements for access network—based on Ethernet Passive Optical Network (EPON) technical requirements 3.0, possessing super EPON access capacity, carrier-class reliability and the complete security function. It can satisfy long-distance optical fiber access requirement on account of its excellent management, maintenance and monitoring capability, abundant service features and flexible network mode. **NETRO NN-EPON-8OLT** can be used with NMS2000 network management system so as to provide users with the perfect solution.

The **NETRO NN-EPON-8OLT** OLT provides 8 *Downstream EPON ports, 4GE * Uplink ETH ports, 2GE * Uplink SFP ports and 2*10G Uplink SFP+ ports. Up to 1:64 Split ratio for up to 512 EPON users. The 1U pizzabox design is for easy installation, Maintenance and Space saving. **NETRO NN-EPON-8OLT** is suitable for Broadcast three in one, video surveillance network, enterprise LAN, Internet of Things, etc.



Specifications:

Network interface	
EPON interface	8 x EPON (1.25/1.25 Gbps)
Uplink Optical Interface	2 x GE SFP + 2 x 10GE SFP+
Uplink Ethernet Interface	4 x RJ-45
PON interface	
EPON	IEEE 802.3ah EPON
Local Management interface	
Console	RJ-45 EIA/TIA-232 Console management port
MGMT	1000BASE-T out-band management port
Performance	
Switching Capacity	64Gbps
Package transmit rate(IPv4/IPv6)	125Mpps

Split ratio	1: 64
Maximum ONU quantity	512 ONT
Power Supply and Consumption	
Power Adaptor	AC Input::100 to 240 V AC, 50/60 Hz; DC Input : 36V-75V
Redundancy Design	Pluggable double power supply, double AC, double DC and AC+DC
Consumption	<56 W
Environmental conditions	
Storage	temperature -10 to 70°C, rel. humidity 10–90% (non-condensing)
Operation	temperature 0 to 45°C, rel. humidity 10–90% (non-condensing)
Physical specifications	
Dimensions	442mm×360mm× 44mm(W * D *H)
Weight	< 5.5 KG

Key Features:

Ethernet switching (L2) features	
VLAN	<ul style="list-style-type: none"> • 4K VLAN entries • Port-based QinQ and Selective QinQ (StackVLAN) • Port-based/MAC-based/IP subnet-based VLA
Spanning tree	<ul style="list-style-type: none"> • IEEE 802.1x STP/RSTP/MSTP • ONU remote loop detection
MAC	<ul style="list-style-type: none"> • MAC Black Hole • Port MAC limit • 8K MAC address
Port	<ul style="list-style-type: none"> • Bi-direction bandwidth control • Port mirroring and traffic mirroring
Service features	
Multicast	<ul style="list-style-type: none"> • IGMPv1/v2/v3 • IGMP Snooping/Proxy • IGMP filtering
Routing	<ul style="list-style-type: none"> • BGP • MPLS • RIP
QoS	<ul style="list-style-type: none"> • Base on port or user-defined rate limitation • Base on port or user-defined priority tag, provide 802.1P, DSCP tag ability of priority • Base on port or user-defined high grade queue scheduling • priority queues and scheduler of SP, WRR and SP+WRR. • Congestion avoidance system
Security features	
User security	<ul style="list-style-type: none"> • Anti-ARP-spoofing deceive defend • Anti-ARP-flooding flooding attack automatic control

	<ul style="list-style-type: none"> • IP, MAC, port and VLAN binding • Port isolation
Device security	<ul style="list-style-type: none"> • Defend DOS attack • Security IP login through Telnet • Hierarchical management and password protection of users • Network security • IP address、VLAN ID、MAC address and port manual binding • Port broadcast /multibroadcast restrain • Base on source / destination MAC address,VLAN,802.1p,ToS,DiffServ,source/ destination • IP(IPv4/IPv6) address,TCP/UDP port number protocol type of IP package flow classify and flow • defined regulation management,support package header 80 byte depth L2-L7 ACLflow filtrate • Dynamic ARP table-based binding • DHCP Option82 and PPPoE+ upload user's physical location
Network security	<ul style="list-style-type: none"> • IP address、VLAN ID、MAC address and port manual binding • Port broadcast /multibroadcast restrain • Base on source / destination MAC address,VLAN,802.1p,ToS,DiffServ,source/ destination • IP(IPv4/IPv6) address, TCP/UDP port number protocol type of IP package flow classify and flow • defined regulation management, support package header 80 byte depth L2-L7 ACLflow filtrate • Dynamic ARP table-based binding • DHCP Option82 and PPPoE+ upload user's physical location
Network management	<ul style="list-style-type: none"> • Command-line interface (CLI) , Console, Telnet and WEB configuration • RMON (Remote Monitoring)1/2/3/9 groups of MIB • System configuration with SNMPv1/v2/v3 • NTP(Network Time Protocol) • NMS2000 network management

Ordering Information:

Model	Description
NN-EPON-8OLT	8*EPON, 4*GE port, 2*GE SFP, 2*10G SFP+, Pluggable Dual Power Supply